THE CLAIMS:

- A method of identifying at least one predominant color in a digital image, the method comprising applying a detection rule to randomly-selected pixels in the image.
- 2. The method of claim 1, wherein the detection rule is applied to a strip of randomly-selected pixels in the image
- The method of claim 1, wherein the detection rule minimizes the probability of at least one of a false-positive outcome and a false-negative outcome.
- 4. The method of claim 3, wherein the probability of a false-positive outcome is the probability of identifying a color having r_c<r_a as a predominant color, where rc is the number of pixels in a sample region having a specific color divided by the total number of pixels in the sample region, and r_a is an acceptable ratio.
- 5. The method of claim 3, wherein the probability of a false-negative outcome is the probability of identifying a color having r_c>r_d as a predominant color, where rc is the number of pixels in a sample region having a specific color divided by the total number of pixels in the sample region, and r_d is a desirable ratio.
- The method of claim 1, wherein the detection rule is used to create a color occurrence list.
- 7. The method of claim 6, wherein the color list is created by testing a first sampling of pixels in the image, for each pixel in the sampling:

if a color vector of the pixel is in the list, incrementing a corresponding counter; and

OT REPORTS

if the color vector is not in the list, adding the color vector to the list and initializing a corresponding counter.

- 8. The method of claim 7, further comprising testing at least one additional sampling of pixels in the image, for each pixel of each sampling: incrementing the corresponding counter if a color vector of the pixel is in the list.
- The method of claim 8, wherein at the end of each additional sampling, all entries with counter q < T_n are removed from the list.
- 10. The method of claim 8, wherein no additional samplings are tested and the list is finalized if the list is empty or all entries have a counter $q > U_n$, whereby all color vectors in the list are identified as the predominant colors.
- 11. The method of claim 6, wherein the color occurrence list is maintained as a sorted list.
- 12. The method of claim 6, wherein the color occurrence list is maintained as a hash table.
- 13. Apparatus for identifying at least one predominant color in a digital image, the apparatus comprising a processor for applying a detection rule to randomly-selected pixels in the image.
- 14. The apparatus of claim 13, wherein the processor determines at least one predominant color for each strip of the image.
- 15. The apparatus of claim 13, wherein the detection rule minimizes the probability of at least one of a false-positive outcome and a false-negative outcome.

- 16. The apparatus of claim 15, wherein the probability of a false-positive outcome is the probability of identifying a color having $r_c < r_a$ as a predominant color, where r_c is the number of pixels in a sample region having a specific color divided by the total number of pixels in the sample region, and r_a is an acceptable ratio.
- 17. The apparatus of claim 15, wherein the probability of a false-negative outcome is the probability of identifying a color having $r_c > r_d$ as a predominant color, where r_c is the number of pixels in a sample region having a specific color divided by the total number of pixels in the sample region, and r_r is a desirable ratio.
- 18. The apparatus of claim 13, wherein the detection rule is used to create a color occurrence list.
- 19. The apparatus of claim 18, wherein the color list is created by testing a first sampling of pixels in the image, for each pixel in the sampling:

if a color vector of the pixel is in the list, incrementing a corresponding counter; and

- if the color vector is not in the list, adding the color vector to the list and initializing a corresponding counter.
- 20. The apparatus of claim 19, further comprising testing at least one additional sampling of pixels in the image, for each pixel of each sampling:

incrementing the corresponding counter if a color vector of the pixel is in the list.

- 21. The apparatus of claim 20, wherein at the end of each additional sampling, all entries with counter $q < T_n$ are removed from the list.
- 22. The apparatus of claim 20, wherein no additional samplings are tested and the list is finalized if the list is empty or all entries have a counter

 $q > U_n$, whereby all color vectors in the list are identified as the predominant colors.

23.An article for a processor, the article comprising computer memory encoded with a program for instructing the processor to identify at least one predominant color in a digital image by applying a detection rule to randomlyselected pixels in the image.